



Product Description

MASTER HPI Plus

Quartz metal halide lamps with opalized outer bulb

Benefits

- High safety and comfort level, maintained over life
- Minimal maintenance cost
- Initial investment saving options with "Plus"-concept and "S" and "P"-types
- Adjustable atmosphere creation by using appropriate color temperature

Features

- Ovoid, internally white coated outer bulb
- Unique 3-band technology resulting in high luminous efficacy, both initially and over long lifetime
- Available in cool white and daylight color appearance demonstrating good color stability
- "S"-type for direct retrofit for HPL lamps
- "P"-type for use without protective front shield

Application

- High bay lighting, e.g. industrial workshops, exhibition halls, hypermarkets, shopping malls, DIY stores, churches, airports and train stations

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury or sodium lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


MASTER HPI Plus

Versions



HPI Plus, E40

Dimensional drawing



Product	D (max)	C (max)
MASTER HPI Plus 400W/645 BU E40 1SL/6	122 mm	290 mm
MASTER HPI Plus 250W/645 BU E40 1SL/12	91 mm	226 mm

MASTER HPI Plus

Controls and Dimming

Dimmable	No
----------	----

General Information

Cap-Base	E40
Life To 10% Failures (Nom)	7500 h
Life To 20% Failures (Nom)	11000 h
Life To 50% Failures (Nom)	20000 h
Life To 5% Failures (Nom)	5000 h
LSF 12000 h Rated	76 %
LSF 16000 h Rated	63 %
LSF 2000 h Rated	99 %
LSF 20000 h Rated	50 %
LSF 4000 h Rated	96 %
LSF 6000 h Rated	93 %
LSF 8000 h Rated	88 %
Operating Position	H15
System Description	BU

Luminaire Design Requirements

Bulb Temperature (Max)	350 °C
------------------------	--------

Light Technical

Color Code	645
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4500 K
Color Rendering Index (Nom)	65
LLMF 12000 h Rated	68 %
LLMF 16000 h Rated	63 %
LLMF 2000 h Rated	90 %
LLMF 20000 h Rated	60 %
LLMF 4000 h Rated	82 %
LLMF 6000 h Rated	77 %
LLMF 8000 h Rated	73 %
Ratio Scotopic/Photopic Lumens	1.50

Mechanical and Housing

Bulb Finish	Coated glass
-------------	--------------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/	Mercury (Hg)
		1000 h	Content (Nom)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	446 kWh	67 mg
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	282 kWh	47 mg

Operating and Electrical (1/2)

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	3.4 A	135 V	115 V	125 V

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	2.2 A	138 V	118 V	128 V

Operating and Electrical (2/2)

Order Code	Full Product Name	Power (Rated) (Nom)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	405 W

Order Code	Full Product Name	Power (Rated) (Nom)
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	256 W

MASTER HPI Plus

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity		Luminous Efficacy	Luminous Flux
		Coordinate X (Nom)	Coordinate Y (Nom)	(rated) (Nom)	(Rated) (Min)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	367	374	80 lm/W	-
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	365	363	66 lm/W	15300 lm

Order Code	Full Product Name	Chromaticity		Luminous Efficacy	Luminous Flux
		Coordinate X (Nom)	Coordinate Y (Nom)	(rated) (Nom)	(Rated) (Min)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	367	374	80 lm/W	-
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	365	363	66 lm/W	15300 lm

Light Technical (2/2)

Order Code	Full Product Name	Luminous Flux (Rated) (Nom)
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	32500 lm

Order Code	Full Product Name	Luminous Flux (Rated) (Nom)
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	17000 lm

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
928074309891	MASTER HPI Plus 400W/645 BU E40 1SL/6	ED120
928076709891	MASTER HPI Plus 250W/645 BU E40 1SL/12	ED90

