



# MASTER PL-C 4 Pin

## MASTER PL-C 26W/840/4P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General information	
Cap-Base	G24Q-3 [ G24q-3]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light technical	
Color Code	841 [ CCT of 4100K (841)]
Luminous Flux (Nom)	1800 lm
Luminous Flux (Rated) (Nom)	1800 lm
Color Designation	Cool White (CW)

Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and electrical	
Power (Rated) (Nom)	26.0 W
Lamp Current (Nom)	0.335 A

# MASTER PL-C 4 Pin

## Temperature

Design Temperature (Nom) 28 °C

## Controls and dimming

Dimmable Yes

## Mechanical and housing

Cap-Base Information 4P

## Approval and application


Mercury (Hg) Content (Nom) 1.4 mg

Energy Consumption kWh/1000 h 29 kWh

## Product data

Full product code	871150062336200
Order product name	MASTER PL-C 26W/840/4P 1CT/5X10BOX
EAN/UPC - Product	8711500623362
Order code	927907384002
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927907384002
Net Weight (Piece)	60.400 g
ILCOS Code	FSQ-26/40/1B-E-G24q=3



## Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 26W/840/4P 1CT/5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	163.9 mm

MASTER PL-C 26W/840/4P 1CT/5X10BOX

## Photometric data



Lightcolor /840

Lightcolor /840

# MASTER PL-C 4 Pin

## Lifetime



### Life Expectancy 3 h cycle

### Life Expectancy 12 h cycle



### Lumen Maintenance 3 h and 12 h cycle

