



# Essential Smart Bright Projector

ST030T LED30/850 35W 220-240V I NB BK

Electronic transformer - Fashion proof optic beam angle 24° - 36°

Essential SmartBright LED Projector is value for money product with high efficacy, good quality and reliability. It offers diverse configurations from 800lm to 3000lm output, and better beam performance with lens design.;It could apply to shopping mall, retail store, It's an ideal product family to distribute in trade market

## Product data

General Information		Service tag	
Light source color	850 neutral white	Service tag	Yes
Number of gear units	1 unit	Operating and Electrical	
Driver/power unit/transformer	ET [ Electronic transformer]	Input Voltage	220 to 240 V
Driver included	Yes	Input Frequency	50 to 60 Hz
Optical cover/lens type	Fashion proof optic beam angle 24°	Power Factor (Min)	0.9
Luminaire light beam spread	36°	Controls and Dimming	
Control interface	-	Dimmable	No
Connection	CI [ Internal connector]	Mechanical and Housing	
Protection class IEC	Safety class I (I)	Housing Material	Aluminum
CE mark	-	Optic material	Polymethyl methacrylate
Warranty period	2 years	Optical cover/lens material	Polymethyl methacrylate
Constant light output	No	Fixation material	Aluminum
Number of products on MCB of 16 A type B	30	Optical cover/lens finish	Textured
EU RoHS compliant	Yes	Overall height	125 mm
Light source engine type	LED		

# Essential Smart Bright Projector

Overall diameter	80 mm
Color	black

## Approval and Application

Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK03 [ 0.3 J]

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	3500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	5000 K
Init. Color Rendering Index	>80
Initial chromaticity	SDCM<6
Initial input power	35 W
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Median useful life L70B50	20000 h
---------------------------	---------

## Application Conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

## Product Data

Full product code	871016332257599
Order product name	ST030T LED30/850 35W 220-240V I NB BK
EAN/UPC - Product	8710163322575
Order code	911401720712
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401720712
Net Weight (Piece)	0.630 kg



## Dimensional drawing



Modular Type	D, mm	H1, mm	H2, mm	H3, mm	L, mm	W, mm
ST030T LED8 & LED12	50	100	174	187	130	51.7
ST030T LED20	60	105	178	191	130	51.7
ST030T LED30	80	125	192	205	180	60

GD391B/RS391B/ST391T Flex Accent G2

