



UniStrip G4

BCP385 30LED 40K 220V A1 L52 DMX

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information			
Light source color	Neutral white	CE mark	CE mark
Light source replaceable	No	Optic type outdoor	Asymmetrical
Number of gear units	1 unit	Number of products on MCB of 16 A type B	4
Driver/power unit/transformer	PSU [Power supply unit]	Light source engine type	LED
Driver included	Yes	Serviceability class	Class B, luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge protection device, front cover and mechanical parts
Optical cover/lens type	GT [Tempered glass]	Light Technical	
Luminaire light beam spread	7.5° x 27°	Standard tilt angle posttop	-
Control interface	Dynamix DMX	Standard tilt angle side entry	-
Connection	Flying leads/wires and 2 Push-in connector 4-pole	Operating and Electrical	
Cable	Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole	Input Voltage	220 to 240 V
Protection class IEC	Safety class I (I)	Input Frequency	50 to 60 Hz
Flammability mark	F [For mounting on normally flammable surfaces]		

UniStrip G4

Inrush current	60 A
Inrush time	0.85 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polymethyl methacrylate
Optical cover/lens material	Glass
Fixation material	Aluminum
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	520 mm
Overall width	88 mm
Overall height	158 mm
Color	Dark gray
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	4032 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	67 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial chromaticity	4 SDCM
Initial input power	60 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-40 to +50 °C
Maximum dim level	10%

Product Data

Full product code	911401751922
Order product name	BCP385 30LED 40K 220V A1 L52 DMX
Order code	911401751922
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401751922
Net Weight (Piece)	2.099 kg



Dimensional drawing



BCP280/383/384/385 UNiStrip G3

UniStrip G4

