



HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSNE 250L 301I TS


The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information		Temperature	
Application Code	L301 ITS	T-Winding (Max)	130 °C
Design	-	Delta-T Normal Conditions	70 °C
Operating and Electrical		Approval and Application	
Input Voltage	220 V	Approval Marks	CE marking
Input Frequency	50 Hz	Product Data	
Power Factor 100% Load (Min)	0.85	Full product code	871829112578500
Mains Voltage Performance (AC)	-8% - +6%	Order product name	BSNE 250L 301I TS
Mains Voltage Safety (AC)	-10% - +10%	EAN/UPC - Product	8718291125785
Input Current with PF Correction	1.4 A	Order code	913713202650
Input Current without PF Correction	3.0 A	Numerator - Quantity Per Pack	1
Power Factor without PF Compensation (Nom)	0.45	Numerator - Packs per outer box	6
Power Losses (Nom)	26 W	Material Nr. (12NC)	913713202650
Wiring		Net Weight (Piece)	2.400 kg
Connector Type	Screw		
System characteristics			
Rated Ballast-Lamp Power	250 W		

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	C1	A1	B1
BSNE 250L 3011 TS	64.5 mm	159.0 mm	72.5 mm

BSNE 250 L301 ITS

